


T-Profile | Shore 80, 84 A



approx. 80° Shore A
Recommended pretension
4...8 %


T-Profile PU 75 A sky blue smooth (8 x 5 mm)



Order No.	Profile dimension	Cross Section cm ²	approx. Weight kg/100 m	Standard Roll		Recommended Min. pulley ∅		Fmax/belt (Standard)*	
	mm			m	ft	mm	inch	kg	lbs
FBSP75A8X5HI	8 x 5	0,25	3,1	50	164	30	1,2	6,0	13,2

* = coefficient of friction μ :0,5

Coefficient of friction μ : Steel: approx. 0,70 | PE: approx. 0,40 | HDPE: approx. 0,35 | FDA/EC/USDA compliant



approx. 84° Shore A
Recommended pretension
4...8 %


T-Profile PU 80 A ultramarine blue smooth (10 x 4,5 mm)



Order No.	Profile dimension	Cross Section cm ²	approx. Weight kg/100 m	Standard Roll		Recommended Min. pulley ∅		Fmax/belt (Standard)*	
	mm			m	ft	mm	inch	kg	lbs
FBT12X45X10L	10 x 4,5	0,27	3,3	50	164	40	1,6	8,1	17,8

* = coefficient of friction μ :0,5

Coefficient of friction μ : Steel: approx. 0,65 | PE: approx. 0,35 | HDPE: approx. 0,30 | FDA/EC/USDA compliant



approx. 84° Shore A
Recommended pretension
4...8 %


T-Profile PU 80 A ultramarine blue smooth (15 x 5 mm)



Order No.	Profile dimension	Cross Section cm ²	approx. Weight kg/100 m	Standard Roll		Recommended Min. pulley ∅		Fmax/belt (Standard)*	
	mm			m	ft	mm	inch	kg	lbs
FBTJ15X5L	15 x 5	0,40	4,8	50	164	40	1,6	9,6	21,1

* = coefficient of friction μ :0,5

Coefficient of friction μ : Steel: approx. 0,65 | PE: approx. 0,35 | HDPE: approx. 0,30 | FDA/EC/USDA compliant



approx. 84° Shore A
Recommended pretension
3...6 %

3L T-Top PU 80 A orange smooth (14,3 x 7,5 mm)



Order No.	Profile dimension	Cross Section cm ²	approx. Weight kg/100 m	Standard Roll		Recommended Min. pulley ∅		Fmax/belt (Standard)*	
	mm			ft	(m)	mm	inch	kg	lbs
FBTJ142X750	14,3 x 7,5	0,72	8,7	100	30,48	80	3,1	17,3	38,1

* = coefficient of friction μ :0,5

Coefficient of friction μ : Steel: approx. 0,65 | PE: approx. 0,35 | HDPE: approx. 0,30 | FDA/EC/USDA compliant