


T-Profiles / Shore 88 A



T-Profile PU 85 A sapphire blue smooth / ribbed** (25 x 5 mm)




Order No.	Profile dimension mm	Cross Section cm ²	approx. Weight kg/100 m	Standard Roll		Recommended Min. pulley Ø		Fmax/belt (Standard)*	
				m	ft	mm	inch	kg	lbs
FBSP85A25X5B	25 x 5	0,59	7,3	30	98,4	50	2,0	15,2	33,4
FBTK25X5LGA (gerillt)	25 x 5	0,59	7,3	30	98,4	50	2,0	15,2	33,4

* = coefficient of friction μ :0,5

approx. 88° Shore A

Recommended pretension
3...6 %

Coefficient of friction μ : Steel: approx. 0,60 | PE: approx. 0,35 | HDPE: approx. 0,30 | FDA/EC/USDA compliant



T-Profile PU 85 A white (20 x 8 mm)



Order No.	Profile dimension mm	Cross Section cm ²	approx. Weight kg/100 m	Standard Roll		Recommended Min. pulley Ø		Fmax/belt (Standard)*	
				m	ft	mm	inch	kg	lbs
FBSP85A20X8W	20x8	0,83	10,0	30	98,4	100	4,0	21,4	47,1


* = coefficient of friction μ :0,5

approx. 88° Shore A

Recommended pretension
3...6 %

Coefficient of friction μ : Steel: approx. 0,60 | PE: approx. 0,35 | HDPE: approx. 0,30 | FDA/EC/USDA compliant

T-Profil 20x8 sapphire blue FBSP85A20X8 on request



T-V-belt PU 90 A red, reinforced aramid

Order No.	Profile dimension mm	Cross Section cm ²	approx. Weight kg/100 m	Standard Roll		Recommended Min. pulley Ø		Fmax/belt (Standard)*	
				m	ft	mm	inch	kg	lbs
FBSL17X13X25	17 x 13 x 25	1,88	23,0	50	164	210	8,3	90,2	198,4
FBSL22X16X25	22 x 16 x 25	2,82	340	30	98,4	280	11,0	135,4	297,9

* = coefficient of friction μ :0,5


approx. 92° Shore A

Recommended pretension
0,5...2 %

Coefficient of friction μ : Steel: approx. 0,50 | PE: approx. 0,30 | HDPE: approx. 0,25



Available cogged on request**



Corn belt PU 80 A orange smooth with/without serrations



Order No.	Profile dimension mm	Cross Section cm ²	approx. Weight kg/100 m	Standard Roll		Recommended Min. pulley Ø		Fmax/belt (Standard)*	
				ft	(m)	mm	inch	kg	lbs
FBSJ8X330G*	33 x 8	1,9	22,8	100	30,48	50	2,0	45,6	100,3
FBSJ8X330GA	33 x 8	1,9	22,8	100	30,48	50	2,0	45,6	100,3

* = coefficient of friction μ :0,5

approx. 84° Shore A

Recommended pretension
3...6 %

Coefficient of friction μ : Steel: approx. 0,65 | PE: approx. 0,35 | HDPE: approx. 0,30 | FDA/EC/USDA compliant