

U-Profile PU 85 A milky smooth




Order No.	Profile dimension mm	Cross Section cm ²	approx. Weight kg/100 m	Standard Roll		Recommended Min. pulley Ø		Fmax/belt (Standard)*	
				ft		mm	inch	kg	lbs
FBSP85A180S1	18 x 11,8	1,70	20,0	1 x 30`5`` / pcs.		120	4,7	43,9	96,6
FBSP85A180S6	18 x 11,8	1,70	20,0	6 x 30`5`` / pcs.		120	4,7	43,9	96,6

Recommended pretension: 3...6 %

* = coefficient of friction μ :0.5

approx. 88° Shore A

Coefficient of friction μ : Steel: approx. 0,60 | PE: approx. 0,35 | HDPE: approx. 0,30 | FDA/EC/USDA compliant



Square-Profile PU 85 A milky smooth




Order No.	Profile dimension mm	Cross Section cm ²	approx. Weight kg/100 m	Standard Roll		Recommended Min. pulley Ø		Fmax/belt (Standard)*	
				ft		mm	inch	kg	lbs
FBSP85A118S1	11,8 x 11,8	1,39	16,7	1 x 30`5`` / pcs.		120	4,7	35,9	79,0
FBSP85A118S6	11,8 x 11,8	1,39	16,7	6 x 30`5`` / pcs.		120	4,7	35,9	79,0

Recommended pretension: 3...6 %

* = coefficient of friction μ :0.5

approx. 88° Shore A

Coefficient of friction μ : Steel: approx. 0,60 | PE: approx. 0,35 | HDPE: approx. 0,30 | FDA/EC/USDA compliant



PU 75 A sky blue smooth with vaulted top




Order No.	Profile dimension mm	Cross Section cm ²	approx. Weight kg/100 m	Standard Roll		Recommended Min. pulley Ø		Fmax/belt (Standard)*	
				m	ft	mm	inch	kg	lbs
FBSP75A0865W	8 x 6,5 (M)	0,39	4,6	50	164	40	1,6	10,0	22,0

Recommended pretension: 4...8 %

* = coefficient of friction μ :0.5

approx. 80° Shore A

Coefficient of friction μ : Steel: approx. 0,70 | PE: approx. 0,40 | HDPE: approx. 0,35 | FDA/EC/USDA compliant



PU 80 A ultramarine blue smooth with vaulted top




Order No.	Profile dimension mm	Cross Section cm ²	approx. Weight kg/100 m	Standard Roll		Recommended Min. pulley Ø		Fmax/belt (Standard)*	
				m	ft	mm	inch	kg	lbs
FBSP80A0865W	8 x 6,5 (M)	0,39	4,6	50	164	50	2,0	11,0	24,2

Recommended pretension: 4...8 %

* = coefficient of friction μ :0.5

approx. 84° Shore A

Coefficient of friction μ : Steel: approx. 0,65 | PE: approx. 0,35 | HDPE: approx. 0,30 | FDA/EC/USDA compliant



PU 85 A sapphire blue smooth with vaulted top



Order No.	Profile dimension mm	Cross Section cm ²	approx. Weight kg/100 m	Standard Roll		Recommended Min. pulley Ø		Fmax/belt (Standard)*	
				m	ft	mm	inch	kg	lbs
FBSP85A0865W	8 x 6,5 (M)	0,39	4,6	50	164	55	2,2	13,2	29,0

Recommended pretension: 4...8 %

* = coefficient of friction μ :0.5

approx. 88° Shore A

Coefficient of friction μ : Steel: approx. 0,60 | PE: approx. 0,30 | HDPE: approx. 0,25 | FDA/EC/USDA compliant